



Ref. Certif. No.

**DK-135346-UL**

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

**CB TEST CERTIFICATE**

Product	AC-DC Power Module
Name and address of the applicant	ARCH ELECTRONICS CORP 3F No 79 Sec 1 Hsin Tai Wu Rd Hsi Chih District New Taipei, 221 Taiwan
Name and address of the manufacturer	ARCH ELECTRONICS CORP 3F No 79 Sec 1 Hsin Tai Wu Rd Hsi Chih District New Taipei, 221 Taiwan
Name and address of the factory	ARCH ELECTRONICS CORP 3F No 79 Sec 1 Hsin Tai Wu Rd Hsi Chih District New Taipei, 221 Taiwan
Note: When more than one factory, please report on page 2	<input type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	Input: 100-240 V a.c., 47-63 Hz, 2.0 A max. <input checked="" type="checkbox"/> Additional Information on page 2
Trademark / Brand (if any)	
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	AJCV100-xS, where "x" can be 9-12.6, 18-25.2 or 36-50.4
Additional information (if necessary may also be reported on page 2)	<b>Additionally evaluated to:</b> EN IEC 62368-1:2020, EN IEC 62368-1:2020/A11:2020 National Differences specified in the CB Test Report.  <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	2210017-CB issued on 2022-11-28

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2022-12-01

Signature: Jan-Erik Storgaard



Ref. Certif. No.

**DK-135346-UL**

**Additional Ratings:**

Output:

For Models "x" can be 9-12.6: 9-12.6 V d.c. 8333 mA (max.), 100 W max.

For Models "x" can be 18-25.2: 18-25.2 V d.c. 4166 mA (max.), 100 W max.

For Models "x" can be 36-50.4: 36-50.4 V d.c. 2083 mA (max.), 100 W max.

**Additional information (if necessary)**



- UL Solutions (US), 333 Pflugsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2022-12-01

Signature:

Jan-Erik Storgaard