

CERTIFICATE OF COMPLIANCE

Certificate Number 20150810-E199779
Report Reference E199779-A34-UL
Issue Date 2015-AUGUST-10

Issued to: ARCH ELECTRONICS CORP
7TH FL-1 79 HSIN TAI WU RD SEC 1
HSIN CHIN
NEW TAIPEI
221 TAIWAN

**This is to certify that
representative samples of**

Component - Power Supplies for Information Technology
Equipment Including Electrical Business Equipment
See addendum page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60950-1 and CAN/CSA C22.2 No. 60950-1-07,
Information Technology Equipment - Safety - Part 1:
General Requirements

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance
capabilities and are intended for use as components of complete equipment submitted for investigation rather
than for direct separate installation in the field. The final acceptance of the component is dependent upon its
installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20150810-E199779
Report Reference E199779-A34-UL
Issue Date 2015-AUGUST-10

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Switching power supply for building-in

Model: MFC15-xy, where:

"x" can be 3,75 ~ 5,25; 6,75 ~ 9,45; 9 ~ 12,6; 11,25 ~ 15,75 or 18 ~ 25,2

"y" can be S, S-A2 or S-A2-DN

MZC20-xy, where:

"x" can be 9 ~ 12,6 or 18 ~ 25,2.

"y" can be S, S-A2 or S-A2-DN

MTC30-xy, where:

"x" can be 3,75 ~ 5,25; 9,0 ~ 12,6; 11,25 ~ 15,75 or 18,0 ~ 25,2

"y" can be S, S-A2 or S-A2-DN

MSC60-xy, where:

"x" can be 3,75 ~ 5,25; 6,75 ~ 9,45; 9 ~ 12,6; 11,25 ~ 15,75 or 18 ~ 25,2

"y" can be S, S-A2 or S-A2-DN



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

