

**Fiber optic connector curing heat oven**

**1 General**

Rugged and easy-to-use FO connector curing heat oven with a variety of features at a low price.

The curing heat oven accommodates up to 24 fiber optic connectors with mit 1.25mm oder 2.5mm ferrules (e. g. F-SMA, F-ST, SC and FC).

The included thermometer allows the monitoring of temperature settings.



Pic. 1 Heating oven with accessories

**2 Features**

- manual temperature setting
- automatic temperature control
- Power „ON“ light indicator
- Heat „ON“ light indicator
- Holding block suitable for F-SMA / F-ST / SC and FC connectors
- Capacity up to 24 FO connectors
- Input voltage 110/220V
- portable (requiring a standard plug outlet 110/220V)
- easy-to-use
- compact and small-size (dimensions: 180 x 140 x 90mm (L x W x H))

**4 Applications**

Due to the variety of features, the FO connector curing heat oven is suitable for:

- Field termination
- supplement to fiber optic connectorization kits

**3 Technical data**

**5 Ordering information**

Specification	Part number
Curing heating oven	910A000100001

Parameter	min.	typ.	max.	Unit
Heating temperature	40		200	°C
Input voltage	100		240	VAC
Power line frequency	50		60	Hz
Power consumption		200		W
Warm up time		15		min
Weight		2		kg
Capacity			24	Pcs.
Power cord length		1.80		m

The information released by Ratioplast-Optoelectronics GmbH in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Ratioplast-Optoelectronics GmbH for its use. Ratioplast-Optoelectronics GmbH reserves the right to change circuitry and specifications at any time without notification to the customer.