



HDTNV2/6B

- Designed for the protection of data and communication lines against longitudinal and transverse surge effects.
 - Pluggable version.
 - No interruption of communication bus when the module is removed.
 - One pair or two pairs lines.
 - Contains both 1st and 2nd stage of protection.
 - The HDTNV*/C range, in addition, contains a gas discharge tube between the PE and SH (shield) terminals for their galvanic isolation.
- The inserted series impedance consists of inductors, which allow the nominal current up to 1,5 A permanently flow through the protection. This predetermines the equipment for protection of the power supply line of the system.
 - It can be used for the protection of analog data lines using the current loop 4 to 20 mA.
 - Not suitable for digital data transmission with high transmission speed.

Type		HDTNV2/6B
Testing category according to IEC 61643-21:2000 and EN 61643-21:2001		C1, C2, C3, D1
Number of pairs		2
Connector type		Screw terminals
Rated operating DC voltage	U _N	0 ÷ 6 V
Maximum continuous operating voltage DC	U _C	7.2 V
Rated load current	I _L	1.5 A
C1 Voltage protection level at I _n (line/PE)	U _p	< 180 V
C1 Voltage protection level at I _n (line/line)	U _p	< 30 V
C1 Nominal discharge current (8/20)	I _n	1 kA
C2 Voltage protection level at I _n (line/PE)	U _p	< 350 V
C2 Voltage protection level at I _n (line/line)	U _p	< 40 V
C2 Nominal discharge current (8/20)	I _n	15 kA
C3 Voltage protection level at 1 kV/μs (line/PE)	U _p	< 15 V
C3 Voltage protection level at 1 kV/μs (line/line)	U _p	< 10 V
D1 Impulse discharge current (10/350) line/PE	I _{imp}	2.5 kA
D1 Total impulse discharge current (10/350)	I _{Total}	5 kA
Response time	t _A	< 30 ns
Series inductance per line		2.2 μH
Parasitic capacitance	C	< 1.5 nF
Lightning protection zone		LPZ 1-2, LPZ 2-3
Housing material		Polyamid PA6, UL94 V-0
Degree of protection		IP20
Operating temperature	θ	-40 ÷ 55 °C
Clamp fastening range (solid conductor)		0.2 ÷ 1.5 mm ²
Tightening moment		0,5 Nm
Installation		On DIN rail 35 mm

Type		HDTNV2/6B
Modular width		1 TE
Operating position		Any
Remote signalling		No
Pluggable version		Yes
Article number of spare module		56 006/M
Lifetime		> 100 000 h
Designed according to standards		
Requirements and test methods for SPDs connected to telecommunications and signalling networks		IEC 61643-21:2000
Safety of Flammability of Plastic Materials		UL 94
Application standards		
Protection against lightning		IEC 62305:2010
Ordering, packaging and additional data		
Mass	m	80 g
Mass (including the packaging)	m	91 g
Packaging dimensions (H x W x D)		26 x 98 x 73 mm
Packaging value	V	0.19 dm ³
ETIM group		EG000021
ETIM class		EC000943
Customs tariff no.		85363010
EAN code		8590681167465
Art. number		56 006/NV



The link in the QR code leads to the online presentation of the **HDTNV2/6B**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit www.hakil.com



8590681167465

Internal diagram

