



1

electromechanical relay 24Vac/dc SPDT 6A-(AC), spring, pluggable



| | |
|--|--|
| Series | CWR |
| Code | X766842S |
| Type | CWRE7-0842-S |
| HS code | 85364190 |
| INPUT TECHNICAL DATA | |
| Input rated voltage | 24 Vac/dc $\pm 10\%$ |
| Pull in / drop out voltage type | 18 V / 1.2 V |
| Current consumption | 7 mA $\pm 10\%$ |
| Turn ON / OFF time | 8 ms / 5 ms |
| Protection circuit | Free-wheel diode, Reverse polarity |
| Connection terminal | 2.5 mm ² (spring) |
| Input channels | 1 pluggable |
| OUTPUT TECHNICAL DATA | |
| Contact type | SPDT, 1 form C, AgSnO ₂ |
| Output voltage | 400 Vac max., 30 Vdc max. |
| Nominal current | 6 A (250 Vac), 6 A (30 Vdc) |
| Connection type | |
| GENERAL TECHNICAL DATA | |
| Operating temperature range | -20...+70°C |
| Input / output isolation | 4 kVac / 60 s |
| Protection degree | IP 20 |
| Overvoltage category / pollution degree | II / 2 |
| Status indication | LED "Input" |
| Housing material | UL94V-0 plastic material |
| Dimensions (LxHxD) | 6.2x89x77 mm |
| Approximate weight | 35 g |
| Mounting information | on a rail, side by side |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| Marking tag | NUPUTUK50 |
| Spare part relay | 8904027 |
| Plugin jumper | CWBK7-0813 (20 poles) |
| APPROVALS AND MARKINGS | CE, |



* Pluggable relay* AC/DC input voltage* SPDT contact* Compact dimensions* Available plug-in jumper for potential distribution* with spring connection
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

DESCRIZIONE DEL PRODOTTO

CWRE7-0842S 1 electromechanical relay 24Vac/dc SPDT 6A-(AC), spring, pluggable