




1 electromechanical relay  
48Vac/dc SPDT 6A, screw, pluggable

|  |   |
|--|---|
| <b>Series</b>                                  | CWR   |
| <b>Code</b>                                    | X766845   |
| <b>Type</b>                                    | CWRE7-0845 (1)  |
| <b>HS code</b>                                 | 85366990  |
| <b>INPUT TECHNICAL DATA</b>                    |   |
| <b>Input rated voltage</b>                     | 48 Vac/dc $\pm 10\%$  |
| <b>Pull in / drop out voltage type</b>         | 36 V / 2.4 V  |
| <b>Current consumption</b>                     | 5 mA $\pm 10\%$   |
| <b>Turn ON / OFF time</b>                      | 8 ms / 5 ms   |
| <b>Protection circuit</b>                      | Free-wheel diode, Reverse polarity  |
| <b>Connection terminal</b>                     | 2.5 mm <sup>2</sup> screw   |
| <b>Input channels</b>                          | 1 pluggable   |
| <b>OUTPUT TECHNICAL DATA</b>                   |   |
| <b>Contact type</b>                            | SPDT, 1 form C, AgSnO <sub>2</sub>  |
| <b>Output voltage</b>                          | 400 Vac max., 30 Vdc max.   |
| <b>Nominal current</b>                         | 6 A (250 Vac), 6 A (30 Vdc)   |
| <b>Connection type</b>                         |   |
| <b>GENERAL TECHNICAL DATA</b>                  |   |
| <b>Operating temperature range</b>             | -20...+70°C   |
| <b>Input / output isolation</b>                | 4 kVac / 60 s   |
| <b>Protection degree</b>                       | IP 20   |
| <b>Overvoltage category / pollution degree</b> | II / 2  |
| <b>Status indication</b>                       | LED "Input"   |
| <b>Housing material</b>                        | UL94V-0 plastic material  |
| <b>Dimensions (LxHxD)</b>                      | 6.2x89x77 mm  |
| <b>Approximate weight</b>                      | 35 g  |
| <b>Mounting information</b>                    | on a rail, side by side   |
| <b>ACCESSORIES</b>                             |   |
| <b>Mounting rail (IEC60715/TH35-7.5)</b>       | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB  |
| <b>Marking tag</b>                             | NUPUTUK50   |
| <b>Plugin jumper</b>                           | CWBK7-0813 (20 poles)   |
| <b>APPROVALS AND MARKINGS</b>                  | CE,  |



\* Pluggable relay\* AC/DC input voltage\* SPDT contact\* Compact dimensions\* Available plug-in jumper for potential distribution  
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical2 (1) Version produced upon request; contact our sales office for availability.

## DESCRIZIONE DEL PRODOTTO

CWRE7-0845 1  
electromechanical relay 48Vac/dc SPDT 6A, screw, pluggable