




Modbus

RTU relay module/ output 4 canali

Series	CIO
Code	XCIO4RLYMB
Type	CIO-4RLY-MB -
HS code	85043129
INPUT TECHNICAL DATA	
Signal type IN	Modbus RTU
Input impedance IN	56 Ω
OUTPUT TECHNICAL DATA	
Signal type OUT	4 NO or NC contacts (programmable)
Output range OUT	2A @ 30 Vdc / 0.3A
Maximum output signal OUT	max. 2A 110 Vdc / 2A 125 Vac
Status indication	LED
Parametrization OUT	Software CaburLab (1)
GENERAL TECHNICAL DATA	
Power supply voltage	24 Vdc (8...30 Vdc)
Current consumption	100 mA (24 Vdc)
Accuracy	0.1% FSR (23°C)
Linearity error	< 0.1% FS
Transmission frequency	10 Hz
Resolution	13 bits
Baud rate	1200 - 230400 bps (programmable)
Parity	None, Odd, Even, Mark, Space
Operation temperature range	-20...+70°C
Insulation	1.5 kVac / 60 s
Insulation type	3-way (IN / OUT / power)
EMC Standard	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3
Overvoltage category / pollution degree	II / 2
Protection degree	IP 20
Connection terminal IN / OUT	2.5 mm ² / 2.5 mm ² (screw)
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	101x79x17.5 mm
Approximate weight	100 g
Mounting information	vertical on a rail, distance 5 mm from adjacent components
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
APPROVALS AND MARKINGS	
	CE



* Output: 5 Vdc 2.5 A max with relay* Insulation: 1.5 kVac, 3-way isolation* 4 output channel* parametrization via Modbus RTU* CaburLab software is available for free
1 Factory setting: Normally Open

DESCRIZIONE DEL PRODOTTO

CIO-4RLY-MB Modbus RTU relay module/ output 4 canali