




1 electromechanical relay 24Vdc
4PDT 6A, screw, pluggable



Series	CM
Code	XCM4C024
Type	CM4C024
HS code	85364190
INPUT TECHNICAL DATA	
Input rated voltage	24 Vdc $\pm 10\%$
Pull in / drop out voltage type	18 V / 2.4 V
Current consumption	40 mA $\pm 10\%$
Turn ON / OFF time	20 ms / 20 ms
Protection circuit	Free-wheel diode
Connection terminal	2.5 mm ² screw
Input channels	1 pluggable
OUTPUT TECHNICAL DATA	
Contact type	4PDT, 4 form C, AgNi
Nominal current	6 A (240 Vac)
Continuous current	12 A
Min applicable load	10 mA / 12 V
Connection type	
GENERAL TECHNICAL DATA	
Operating temperature range	-20...+60°C
Input / output isolation	2.5 kVac / 60 s
Protection degree	IP 20
Oversoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	27x75x68 mm
Approximate weight	54 g
Mounting information	on a rail, side by side
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Marking tag	already mounted
Spare part relay	8904069
Plugin jumper	CMB27B (6 poles)
APPROVALS AND MARKINGS	CE



* Pluggable relay* DC input voltage* 4PDT contact* Compact dimensions* Available plug-in jumper for potential distribution
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

DESCRIZIONE DEL PRODOTTO

CM4C024 1
electromechanical relay 24Vdc 4PDT 6A, screw, pluggable