


**Diodes**  
redundancy module 12-24-48 Vdc 2x15 A

<b>Code</b>	XCSBD
<b>Type</b>	CSBD -
<b>HS code</b>	8504909000
<b>INPUT TECHNICAL DATA</b>	
<b>Input rated voltage</b>	12-24-48 Vdc
<b>Input nominal current</b>	2 x 15 A
<b>OUTPUT TECHNICAL DATA</b>	
<b>Output voltage range</b>	12-24-48 Vdc selectable
<b>Output adjustable range</b>	1 x 15 A (max. 30 A peak)
<b>IN-OUT voltage drop</b>	0.7 V a 15 A
<b>Status indication</b>	LED "DC OK"
<b>Alarm contact</b>	2 dry contacts, max. 1A
<b>GENERAL TECHNICAL DATA</b>	
<b>Operating temperature range</b>	-20...+50°C
<b>Overvoltage category / pollution degree</b>	II / 2
<b>Protection degree</b>	IP 00
<b>Connection terminal</b>	2.5 mm <sup>2</sup> / 2.5 mm <sup>2</sup>
<b>Housing material</b>	UL94V-0 plastic material
<b>Dimensions (LxHxD)</b>	40x130x85
<b>Approximate weight</b>	120 g
<b>Mounting information</b>	vertical on a rail, 10 mm from adjacent components
<b>ACCESSORIES</b>	
<b>Mounting rail (IEC60715/TH35-7.5)</b>	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
<b>Mounting rail (IEC60715/TH35-15)</b>	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
<b>APPROVALS AND MARKINGS</b>	CE



\* Suitable for connecting power supplies without ORing diodes\* 12, 24 and 48 Vdc selectable operating voltages\* 2 alarm relays\* Compact dimensions

**DESCRIZIONE DEL PRODOTTO**

CSBD Diodes redundancy module 12-24-48 Vdc 2x15 A