

## USB 2.0 panel plug with cable



<b>Code</b>	XPSPUSB2M60AA
<b>Type</b>	PSP-USB2/M60/AA
<b>HS code</b>	-, TEST
<b>GENERAL TECHNICAL DATA</b>	
<b>Type of connection outside</b>	USB 2.0 type A connector
<b>Type of connection inside</b>	60 mm cable with USB 2.0 type A connector
<b>Contact surface</b>	Gold over nickel
<b>Plugging cycles</b>	5000
<b>Operating temperature range</b>	-25...+55°C
<b>Standard / approvals</b>	IEC 62321-5:2013
<b>Category</b>	USB 2.0 Type A
<b>Protection degree</b>	IP65 with rubber cap closed
<b>Housing material</b>	Aluminium
<b>Dimension</b>	21.2 mm M22
<b>Approximate weight</b>	45 g
<b>Mounting information</b>	On panel with hole diameter 22mm, thickness 1...10 mm
<b>Fixing</b>	Fixing with threaded ring on the back (without screws)
<b>APPROVALS AND MARKINGS</b>	
	CE
<b>ACCESSORIES</b>	
<b>Ricambi</b>	Rubber cap code XPSPCAP1



## DESCRIZIONE DEL PRODOTTO

PSP-USB2/M60/AA USB 2.0 panel plug with cable