


1 electromechanical relay 24Vdc
SPST(NA) 5A, screw, not pluggable

| | |
|---|---|
| Series | |
| Code | XRFA024D |
| Type | RFA024D (1) |
| HS code | 85364190 |
| INPUT TECHNICAL DATA | |
| Input rated voltage | 24 Vdc $\pm 10\%$ |
| Pull in / drop out voltage type | 18.4 V / 2.4 V |
| Current consumption | 15 mA $\pm 10\%$ |
| Turn ON / OFF time | 15 ms / 5 ms |
| Protection circuit | Free-wheel diode, Reverse polarity |
| Connection terminal | 2.5 mm ² screw |
| Input channels | 1 not pluggable |
| OUTPUT TECHNICAL DATA | |
| Contact type | SPST(NO), 1 Form A (NO), AgSnO ₂ |
| Nominal current | 5 A (250 Vac) |
| Continuous current | 10 A |
| Min applicable load | 100 mA / 5 Vdc |
| Connection type | |
| GENERAL TECHNICAL DATA | |
| Operating temperature range | -20...+70°C |
| Input / output isolation | 2.5 kVac / 60 s |
| Protection degree | IP 00 |
| Overvoltage category / pollution degree | II / 2 |
| Status indication | LED "Input" |
| Housing material | UL94V-0 plastic material |
| Dimensions (LxHxD) | 12x77x52 mm |
| Approximate weight | 30 g |
| Mounting information | on a rail, side by side |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| Mounting rail (IEC60715/TH35-15) | PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB |
| Spare part relay | 8904075 |
| APPROVALS AND MARKINGS | CE, |



* Not-pluggable relay
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical2 (1) Version produced upon request; contact our sales office for availability.

DESCRIZIONE DEL PRODOTTO

RFA024D
1 electromechanical relay 24Vdc SPST(NA) 5A, screw, not pluggable