




10/100Mbps fast  
ethernet switch 5-RJ45, unmanaged

<b>Series</b>	SWE-F
<b>Code</b>	XSWEF05PU
<b>Type</b>	SWE-F-05PU
<b>HS code</b>	-
<b>Version</b>	5 – RJ45 unmanaged
<b>Interface</b>	
<b>Number and type of interface</b>	5 RJ45 ports
<b>Connection method</b>	Auto negotiation and auto crossing
<b>Transmission speed</b>	10/100 Mbps
<b>MAC table size</b>	1 K
<b>Status indication</b>	Power, Link/Speed, Link /Activity
<b>GENERAL TECHNICAL DATA</b>	
<b>Power supply voltage</b>	5...58 Vdc
<b>Current consumption</b>	< 300 mA
<b>Operating temperature range</b>	-40...+60°C
<b>Ambient temperature range</b>	-40...+85°C
<b>Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
<b>Safety Standard</b>	EN 62368-1
<b>EMC Standard</b>	EN/IEC 61000-3-2; EN61000-3-3
<b>Overvoltage category /pollution degree</b>	1 / 2
<b>Protection degree</b>	IP20
<b>Connection type</b>	1.5 mm <sup>2</sup> (screw)
<b>Housing material</b>	metallic
<b>Dimensions (LxHxD)</b>	30x118x80 mm
<b>Approximate weight</b>	406 g
<b>Mounting information</b>	on a rail, side by side
<b>APPROVALS AND MARKINGS</b>	CE
<b>ACCESSORIES</b>	
<b>Mounting rail (IEC60715/TH35-7.5)</b>	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
<b>Mounting rail (IEC60715/TH35-15)</b>	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB



## DESCRIZIONE DEL PRODOTTO

SWE-F-05PU 10/100Mbps fast  
ethernet switch 5-RJ45, unmanaged