




## 10/100Mbps slim fast ethernet switch 8-RJ45, unmanaged

|   |  |
|---|--|
| <b>Series</b>                                 | SWE-T  |
| <b>Code</b>                                   | XSWET8PU   |
| <b>Type</b>                                   | SWE-T-8PU  |
| <b>HS code</b>                                | 85176200   |
| <b>Version</b>                                | 8 – RJ45 unmanaged   |
| <b>Interface</b>                              |  |
| <b>Number and type of interface</b>           | 8 RJ45 ports   |
| <b>Connection method</b>                      | Auto negotiation, Full/Half duplex mode, auto MDI/MDI-X connection           |
| <b>Transmission speed</b>                     | 10/100 Mbps  |
| <b>MAC table size</b>                         | 2K   |
| <b>Status indication</b>                      | Power, Link/Speed, Link /Activity  |
| <b>GENERAL TECHNICAL DATA</b>                 |  |
| <b>Power supply voltage</b>                   | 12...36 Vdc / 10...24 Vac  |
| <b>Current consumption</b>                    | 170 mA   |
| <b>Operating temperature range</b>            | -10...+60°C  |
| <b>Ambient temperature range</b>              | -10...+60°C  |
| <b>Standards</b>                              | IEEE802.3, 802.3u, 802.3x  |
| <b>Safety Standard</b>                        | EN 62368-1   |
| <b>EMC Standard</b>                           | EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-6-2 |
| <b>Overvoltage category /pollution degree</b> | I / 2  |
| <b>Protection degree</b>                      | IP 30  |
| <b>Connection type</b>                        | 1.5 mm <sup>2</sup> (screw)  |
| <b>Housing material</b>                       | metallic   |
| <b>Dimensions (LxHxD)</b>                     | 24x145x75 mm   |
| <b>Approximate weight</b>                     | 465 g  |
| <b>Mounting information</b>                   | on a rail, side by side  |
| <b>APPROVALS AND MARKINGS</b>                 | FC, CE,  |
| <b>ACCESSORIES</b>                            |  |
| <b>Mounting rail (IEC60715/TH35-7.5)</b>      | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB                                     |
| <b>Mounting rail (IEC60715/TH35-15)</b>       | PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB                                     |



\* 5 and 8 port fast ethernet switch unmanaged\* Designed to meet Level 3 (Heavy) industrial environments\* Panel and DIN rail mountable

## DESCRIZIONE DEL PRODOTTO

SWET-8PU  
10/100Mbps slim fast ethernet switch 8-RJ45, unmanaged