



EV charger Easy series 22kW with integrated cable

Series	EASY
Code	EVEASY22C
Type	EVEASY22C
HS code	85437090
PRODUCT INFORMATION	
Power	3.5 – 22 kW
Charging Mode	MODE 3 CASE C (with cable 5m)
Connector standard	Type 2
Dimensions (W x H x D)	355x650x150 mm
Weight	12 Kg
Enclosure Material	PC+ASA (UL94-V0)
Mounting	Wall / Stand
GENERAL FEATURES	
Voltage	400V±15% (three phase) 230 V±15% (single phase)
Frequency	50/60Hz
Network Configuration	TN/TT/IT(3P+N+T o 3P+T) TN/TT/IT(1P+N+T o 2P+T)
Earth Leakage Protection	DC Leak (6 mA)
User interface	APP Control
Start/Stop Charge	Plug-in
Communications signals	LED Light belt (red, blue, green)
Power metering	None
Additional	Wifi (Access Point) Hotspot
Power Management	Static (Max power adjustable by App or selector)
PhotoVoltaic integration	–
Dry contact	–
Communication Protocol	None
Reports	Charge reports / Fault reports
Protections	Overcurrent protection; Overvoltage protection; Undervoltage protection; Relay over temperature protection; Socket or plug over temperature protection; CP fault protection; Relay adhesion protection
IP Degree	IP54
IK Protection degree (20°C)	IK8
Ambient Temperature	-25°C +50°C
Operating Humidity	≤95%HR
Standards	IEC 61851-1; IEC 61851-21-2 (EMC class B); IEC 62196-2; EN 300 328 (RED WiFi 2.4GHz); EN 301 489-1/17 (RF-EMC); EN 62311 (Health)
APPROVALS AND MARKINGS	 



* Stylish and compact design* Charging Mode: MODE 3, with cable and cable holder (CASE C)* Connector standard Type 2* WI-FI connectivity in Access Point mode* Plug in start charging* Web App configuration management* DC Earth Leakage Protection 6mA* Wall or stand mounting

DESCRIZIONE DEL PRODOTTO

EV charger Easy series 22kW with integrated cable